



**ZEON CHEMICALS L. P.**

# Material Safety Data Sheet

Form: 245  
Issue Date: 11/08/06  
Supersedes: 10/13/04  
MSDS Number: Z01599

## Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Manufacturer / Importer:**  
Zeon Chemicals L.P.  
4111 Bells Lane  
Louisville, Kentucky 40211

**Telephone Number:**  
1-800-735-3388  
(502)-775-2000

**Emergency Telephone Number:**  
1-800-776-2460 Ext 7650  
(502) 774-8126

**Chemical Family:**  
Methyl Styrene / Chloromethyl  
Acrylate Copolymer in  
Anisole

**Uses:**  
Electronic Applications

This MSDS applies to the following product(s):

**ZEP 520A**

## Section 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Amount	Exposure Limits	
			OSHA PEL	ACGIH TLV
Anisole	100-66-3	89 %	None Established	None Established

Other Ingredients	CAS #	Amount	Notes
Methyl Styrene / Chloromethyl Acrylate Copolymer	43127-35-1	11 %	TWA = Time Weighted Average TLV = Threshold Limit Value AL = Action Level RD = Respirable Dust TD = Total Dust STEL = Short Term Exposure Limit Skin = Skin contact may be a significant route of exposure A1 = ACGIH confirmed Human Carcinogen A2 = ACGIH Suspected Human Carcinogen A3 = ACGIH Animal Carcinogen A4 = ACGIH Not Classifiable as a Human Carcinogen

### Section 3 - HAZARDS IDENTIFICATION

<b>Emergency Overview:</b>	This material is a transparent, colorless to pale yellow liquid with a sweet odor. Combustible liquid and vapors. Harmful if ingested, inhaled, or absorbed through the skin. May produce vapors or mists that can cause eye, skin, and respiratory tract irritation. Prolonged or repeated exposure to vapors may cause drowsiness, nausea, dizziness, or headaches. Toxic combustion products may be released under fire conditions
----------------------------	---

**Potential Health Effects From Overexposure:** Possible routes of entry include skin & eye contact and process vapor or mist inhalation.

Contains Anisole. Contact with liquid, vapors, or mists may cause irritation to the eyes and skin. Inhalation of vapors or mists may cause irritation of the nose, throat, and respiratory tract. Inhalation of high vapor or mist concentrations may produce narcotic effects, CNS depression, unconsciousness, and death. Accidental ingestion may cause gastrointestinal irritation, nausea, vomiting, and diarrhea and possible liver or kidney effects. Processing under conditions of inadequate ventilation may produce symptoms of coughing, tearing, difficult breathing, drowsiness, nausea, dizziness, or headaches.

Appropriate precautions should be taken to minimize potential exposure to accidental ingestion, inhalation of process vapors or mists, and skin contact.

Overexposure to decomposition or combustion products may cause irritation of the eyes, skin, and respiratory tract. Symptoms such as coughing, tearing, and irritation should be regarded as potentially hazardous and measures taken to avoid exposure. See Section 10 for information on combustion products.

### Section 4 - FIRST AID MEASURES

If irritation occurs or persists from any route of exposure, remove the affected individual from the area and seek medical assistance.

**Ingestion:** If swallowed, seek medical assistance immediately. Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

**Vapor Inhalation:** Remove the affected individual to fresh air. If breathing has stopped, administer artificial respiration and seek medical assistance immediately.

**Eye Contact:** Flush eyes with running water for several minutes while holding eyelids open. Consult a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing. Wash contact area with soap and water for 15 minutes. Seek medical attention if irritation / allergic skin reaction develops. Launder contaminated clothing before reuse.

### Section 5 - FIRE FIGHTING MEASURES

**Extinguishing Media:** Carbon dioxide, dry chemical, water fog or alcohol resistant foam is recommended for small fires. For large fires use aqueous foam or water fog. Use water spray or fog to cool fire exposed containers.

**Special Firefighting Procedures:** Wear positive pressure self-contained breathing apparatus (SCBA) during the attack phase of firefighting operations and during cleanup in enclosed or poorly ventilated areas immediately after a fire. Personnel not having suitable respiratory protection must leave the area to prevent significant exposure to toxic combustion gases from any source.

**Unusual Fire and Explosion Hazards:** Combustible liquid and vapors. Explosive vapor - air mixtures may form above the flash point. Vapor can flow along surfaces to distant ignition sources and flash back. Closed containers may rupture due to pressure buildup under fire conditions. Toxic gases may be formed upon combustion and represents a hazard to firefighters. See Section 10 for additional information on combustion products.

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

Wear respiratory protection and protective clothing, ventilate area, remove all ignition sources, and use non-sparking tools and equipment to contain spill and recover as much as possible. Absorb remaining residue with inert material and place into closed containers to await disposal. Do not allow product to enter municipal sewers or waterways. Spills or releases to the environment may be reportable to the National Response Center (800) 424-8802 and to state and / or local agencies.

## Section 7 - HANDLING AND STORAGE

---

Use only in well ventilated areas. Avoid contact with eyes, skin, and clothing. Store in a well ventilated location away from heat, sparks, flame, and direct sunlight. Keep container closed when not in use. Do not eat, smoke, or drink where this product is handled, processed, or stored. Wash hands thoroughly before eating or smoking. Evaluate transfer operations for potential static charge buildup and ground and bond accordingly. Use non-sparking tools and equipment. Empty containers may retain product residue (liquid and / or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks, open flames, or incompatible materials.

## Section 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Ventilation:** Enclose operations and / or provide local exhaust ventilation to draw fumes, vapors, or mists away from workers. Ventilation must be adequate to maintain the ambient workplace atmosphere below the limits listed in Section 2.

**Respiratory Protection:** For protection against process vapors or mists, wear a NIOSH approved respirator suitable for the anticipated airborne concentration. Wear a positive pressure air-supplied respirator in situations where there may be potential for elevated airborne exposure.

**Protective Equipment:** During processing operations, splash proof goggles or safety glasses with face shield suitable for keeping liquid material out of the eyes should be worn when potential exists for eye contact. Rubber gloves and apron should be worn when skin contact is anticipated. Provide an eye wash facility and safety shower.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

Specific Gravity (H <sub>2</sub> O=1): ~1.0	Solubility in Water: Insoluble	% Volatile by Weight: 89
Flash Point: 126° F (52° C)	Boiling Point: 313° F (156° C)	Vapor Density (Air =1): 3.7
Vapor Pressure: 10 mm Hg @ 108° F (42° C)	Evaporation Rate (BuAc=1): No Data	Autoignition Temp: 887° F (475° C)

Appearance and Odor: Transparent, colorless to pale yellow liquid with a sweet odor.

## Section 10 - STABILITY AND REACTIVITY

---

**Stability:** Stable under ordinary conditions of use and storage.

**Conditions to Avoid:** Overheating, open flames, sparks, and contact with ignition sources and incompatibles.

**Materials to Avoid:** Oxidizing agents, strong, acids, formaldehyde.

**Hazardous Decomposition Products:** Fumes produced when heated to decomposition temperatures may contain carbon monoxide, carbon dioxide, hydrochloric acid, chlorine, aliphatic and aromatic hydrocarbons. Combustion products must be considered toxic

## Section 11 - TOXICOLOGICAL INFORMATION

---

The following information on Anisole was obtained from RTECS and other literature sources:

Oral LD<sub>50</sub> (rat) - 3700 mg/kg

Skin Irritation (rabbit) - 500 mg/24H; moderate

Oral LD<sub>50</sub> (mouse) - 2800 mg/kg

Inhalation LC<sub>50</sub> (rat) - >5000 mg/m<sup>3</sup>

## Section 12 - ECOLOGICAL INFORMATION

---

No specific information available.

## Section 13 - DISPOSAL CONSIDERATIONS

---

Waste resulting from this product as supplied may be classified as hazardous because of ignitability per the current listings and characteristics contained in 40 CFR Part 261, and its Appendices. It is the generator's responsibility to determine, per the regulation, the applicability of the Resource Conservation and Recovery Act (RCRA), as well as all state, local, or other governmental agency waste disposal regulations, to the particular waste materials prior to treatment or disposal. Disposal of liquid wastes and solids containing free liquids by land filling is prohibited in most jurisdictions. Incinerate or use biological treatment in accordance with federal, state, and local regulations. Containers of this product may be hazardous when emptied. Empty containers may retain product liquid and vapors.

## Section 14 - TRANSPORTATION INFORMATION

---

For domestic transportation purposes, this product is defined or designated as a hazardous material by the U.S. Department of Transportation under Title 49 of the Code of Federal Regulations.

DOT Hazard Class	3
DOT Proper Shipping Name	Anisole Mixture, 3, UN 2222, PG III
DOT Label	3
UN/NA Hazard No.	UN 2222
	Marine Pollutant

## Section 15 - REGULATORY INFORMATION

---

**TSCA Inventory Status:** This product and all components are either listed on the U.S. EPA Toxic Substances Control Act Inventory or meet exemption criteria.

**TSCA 12(b) Export Notification Status:** This product does not contain any components subject to export notification requirements.

**SARA 313 Status:** This product does not contain any components exceeding the *de minimis* amount subject to reporting under Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

**Additional Right-to-Know Information on Components:**

Component	CAS #	Key (See below)	
Anisole	100-66-3	7, 10, 14	*
Methyl Styrene / Chloromethyl Acrylate Copolymer	43127-35-1	7, 13	*

Key	Description	Key	Description
1.	Reserved	8.	MA Extraordinary Hazardous Substance above 1 ppm
2.	CA Listed Carcinogen	9.	MA Toxic or Hazardous Substance above 1%
3.	CA Listed Reproductive Toxin	10.	NJ Hazardous Substance above 1%
4.	PA Special Hazardous Substance above 0.01%	11.	NJ Special Health Hazard Substance above 0.1%
5.	PA Hazardous Substance above 1%	12.	NJ Environmental Hazardous Substance above 1%
6.	PA Non-Hazardous Substance above 3%	13.	NJ Non-Hazardous Substance above 1%
7.	PA Non-Hazardous Substance above 5%	14.	Canadian WHMIS Ingredient Disclosure List Substance

**Section 16 - ADDITIONAL INFORMATION****Hazard Rating System Classifications:**

	NFPA	HMIS	Key: 0=least; 1=slight; 2=moderate; 3=high; 4=extreme
<b>Health</b>	1	1	National Fire Protection Association rating identifies hazards during a fire emergency.
<b>Flammability</b>	2	2	Hazardous Materials Identification System rating applies to products as packaged.
<b>Reactivity</b>	0	1	

It may be possible under certain processing and handling conditions, e.g. processes that create vapors, mists, or dust, to release unreacted monomers and other substances in airborne concentrations in excess of their established exposure limits or guidelines. Customers and processors should do sufficient in-house industrial hygiene monitoring to assure compliance of their operations.

**Reason for (Re)issue:** Revise Sections 9, 11, 13, 16

**User's Responsibility**

This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of your operation must be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin must be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

**Disclaimer of Liability**

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user.